



825 Electrical Tape

Premium Profession Grade Vinyl Tape , coated with a synthetic-rubber based adhesive, 105°C.

FEATURES:

- Rubber adhesive
- PVC carrier

BENEFITS:

- All-weather vinyl insulating tape
- Flame retardant
- UV resistant
- Excellent resistance to abrasion, moisture, Alkalis and acids
- Excellent low and high temperature performance
High tensile and mechanical strengths in cold situation
- Extremely flexible, even in cold weather
Inhibits corrosion of electrical conductors
Compatible with all standard cable insulations



STANDARD SIZES:

Length: 9m, 20m, 33m

Width: 19mm, 25mm

Core ID: 25.4mm, 38mm

COLORS:

Black	White	Yellow
Red	Blue	Green
Gray	Violet	Brown

Other sizes and colors are available on request.

Properties	Value	Unit	Test Method
Total thickness	0.180±0.008	mm	ASTM D1000
Tensile strength	≥25	N/cm	ASTM D1000
Elongation at break	≥100	%	ASTM D1000
Adhesion strength			ASTM D1000
— to steel	≥1.75	N/cm	
— to backing	≥1.75	N/cm	
Flammability	B(self-extinguishing)	mm/min	ISO 3795
Dielectric Strength	≥39.37	kV/mm	ASTM D1000
Volume resistivity	≥10 ¹²	Ω·in	ASTM D1000
Temperature class	80	°C	UL 510
	105	°C	CSA

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES:

It is specifically designed for used for wrapping electric wires and cables etc. wrapped wires with a half-lap is best, The last layer should be no tension to prevent flagging.

STORAGE AND SHELF LIFE

The shelf life of the product is two years when stored at 20-30°C, max 65% relative humidity and out of direct sunlight, in original packaging.

All technical information and data mentioned are provided to the best of our knowledge on the basis of our lab tests believed to be reliable. They shall be considered as typical values and are not appropriate for a specification. Therefore, all statements, technical information and recommendations concerning products sold or samples provided by Avery Dennison Yongle do not constitute a guarantee or warranty. All products are sold with the understanding that the user has independently determined the suitability of such products for its application purposes.

©2021 Avery Dennison Corporation. All rights reserved. Avery Dennison Yongle is a trademark of Avery Dennison Corporation. Plyon and all other Avery Dennison brands, product names or service programs are trademarks of Avery Dennison Corporation.



Avery Dennison Yongle Tape

No.9 East Yangi Road, Industrial Park,
Zhuzhou, Hebei, P.R. China
Post code: 072750

TEL: 0510-82021817 / 13921396678

For more information on our tapes and adhesive solutions, visit www.yongletape.com.cn